

<b>MODÈLE LOG GRAPPLE (ATV)</b>	<b>950L</b>
A- Maximum boom reach	9' 6" / 2.9m
D- Minimum boom reach	32 3/4" / 83,2cm
E- Grapple model	léger
F- Maximum grapple opening	31" / 0.79m
G- Minimum grapple closing	3" / 7,6cm
I- Grapple rotation	continuous
J- Boom rotation	345°
L- Stabilizer reach during work mode	78" / 1,98m
N-Boom height	70" / 1,78m
1- Boom rotation	motor
2- Stabilizer cylinder	2" / 5.08m
3- Boom cylinder	2 ½" / 6.35cm
4- Forears cylinder	2 ½" / 6.35cm
5 - Grapple cylinder	2 ½" / 6.35cm
6- Lift capacity at maximum boom reach	650lbs / 295kg
7 - Lift capacity at minimum boom reach	1 600lbs / 725kg
8- Grapple weight*	96lbs / 43kg
9- Total loader weight	1350lbs / 614kg
12- Manual valve	X
13- Grapple motor (capacity)	2 248lbs / 1 022kg
Hydraulic power pack trailer mounting	6 HP, 2GPM
Overall length	11' 7" / 3,53m
Overall width	48" / 1,22m
Overall height	70" / 1,78m
Ground clearance	11" / 28cm
Load length	7' / 2,14m
Volume capacity	0,33 cord / 1.22m <sup>3</sup>
Load capacity	2,75 ton / 2500kg
Jack	Yes
Hitch	Ball
Axle diameter	1,5625 / 4cm
Tire size	175/80D13
Adjustable tandem	Hydraulic
Hydraulic winch	Option
Dumping box	Option
Bucket + cylinder	Option

\*Incluant le moteur et la liaison \*Nous recommandons un VTT de 400cc et plus

N.B.- Ces données sont calculées selon les normes S.A.E et peuvent varier, - La conception et les spécifications peuvent être modifiées sans préavis.